




VF100 FLOW METER

VF100 SERIES 浮子式流量計



Flow Range:
 0.5-5 L / Min
 1-10 L / Min
 2-25 L / Min
 5-50 L / Min
 10-100 L / Min




SPECIFICATIONS

Service: gases.
 Wetted Materials:
 Body:Acrylic plastic.
 O-ring:Buna-N(Fluoroelastomer available).
 Metal Parts:Brass standard,stainless steel optional.
 Temperature&Pressure Limits:
 Without valve:100psi (6.9bar)@150 °F (65°C) ;
 150psi (10bar)@100 °F (38°C).
 With valve: 100psi (6.9bar)@120 °F (48°C).
 Accuracy: 3% of full scale.
 Process Connection:1/8 female NPT.
 Mounting Orientation: Mount in vertical Position.
 Weight: (0.12kg)


VF100 Dimension-MM	
A	102mm
B	76mm
C	41.2mm
D	31.7mm
E	52.4mm
F	105mm
G	25mm

VFR100 FLOW METER

VFR100 SERIES 浮子式流量計



Flow Range:
 200-2500 C.C / Min
 2-25 L / Min
 5-50 L / Min
 10-100 L / Min
 50-300 L / Min



SPECIFICATIONS

Service: gases.
 Wetted Materials:
 Body: polycarbonate.
 O-ring:Neoprene &Buna-N.
 Temperature Limit: 130 °F (54°C).
 Pressure Limit: 100psi (6.9bar).
 Accuracy: 3 % .
 Process Connection:1/8 female NPT.
 Weight: (0.12kg)

VFR100 Dimension-MM	
A	116mm
B	76mm
C	41.2mm
D	30.2mm
E	54mm
F	122.6mm or 217mm
G	25mm