

VWR FLOW METER (Relay)

VWR SERIES (Relay) 浮子式流量開關



SPECIFICATIONS

Service: water.
 Wetted Materials:
 Body: Acrylic plastic.
 O-ring: Buna-N (Fluoroelastomer available).
 Metal Parts: Brass standard, stainless steel optional.
 Temperature & Pressure Limits:
 Without valve: 100psi (6.9bar) @ 150 °F (65°C) ;
 150psi (10bar) @ 100 °F (38°C) .
 With valve: 100psi (6.9bar) @ 120 °F (48°C) .
 Accuracy: 3% of full scale.
 Process Connection: 1/8 female NPT.
 Mounting Orientation: Mount in vertical Position.

Flow Range:
 2 L / Min
 5 L / Min
 測量範圍可依規格訂製

VF FLOW METER

VF SERIES 微量浮子式流量計



SPECIFICATIONS

Service: gases.
 Wetted Materials:
 Body: polycarbonate.
 O-ring: Neoprene & Buna-N.
 Temperature Limit: 130 °F (54°C) .
 Pressure Limit: 100psi (6.9bar).
 Accuracy: 3% .
 Process Connection: 6mm.

Flow Range:
 600 C.C / Min
 1000 C.C / Min
 1 L / Min
 2 L / Min
 3 L / Min
 測量範圍可依規格訂製